

Value-packed and stylish

The 19" ViewSonic VE920m LCD monitor is the ALL-IN-ONE PRICE-PERFORMANCE SOLUTION FOR MIXED DATA, AUDIO, GRAPHICS AND VIDEO CONTENT. This LCD is packed with features not normally found in a value display. CLEARMOTIV™ BROADCAST-QUALITY VIDEO, 8ms response, a high 400:1 (typ.) contrast ratio and a horizontal viewing angle of up to 160° all ENSURE INTENSE VISUAL PERFORMANCE. The height adjustability and tilt function provide more flexibility and better ergonomic working conditions. Enjoy a true multimedia experience with less clutter and components on the desktop. Look to the VE920m LCD monitor for affordability without compromise for small/home office, corporate, government or education use.

VE920m

**ERGONOMIC
19" LCD MONITOR
WITH MULTIMEDIA**



AFFORDABILITY WITHOUT COMPROMISE

- > **ClearMotiv™ 8ms video response time**
Fast 8ms video response delivers broadcast-quality full motion video.
- > **Dynamic Structure™ technology**
Innovative liquid crystal composition and pixel matrix accelerate video response for seamless video and intense graphics.
- > **Multimedia enhanced**
Save workspace with bezel-integrated stereo speakers.
- > **Adaptable ergonomics - Height adjustable and tilt**
Provides the most comfortable viewing position for the user, enabling superior comfort.
- > **Stylish slim-bezel design**
An ultra-thin bezel lets you see more without taking up valuable real estate.
- > **Ultra-high 280cd/m² brightness (typ.) and 400:1 contrast ratio (typ.) for rich, detailed images**
- > **OnView® controls for superior screen adjustability**
- > **Full 19" viewable screen with 1280 x 1024 resolution**
- > **VESA® 100mm wall mount interface and Kensington® security port**
- > **PC and Mac® compatible**
- > **TCO'03 and Energy Star® qualified**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

VE920m

ERGONOMIC 19" LCD MONITOR WITH MULTIMEDIA



LCD	Type	19" TN colour TFT active matrix SXGA LCD
	Display Area	37.6cm horizontal x 30.1cm vertical; 48.3cm diagonal
	Pixel Pitch	0.294mm
	Optimum Resolution	1280 x 1024
	Pixel Clock	135MHz
	Contrast Ratio	400:1 (typ.)
	Viewing Angles	150° horizontal, 130° vertical (at 10:1) 160° horizontal, 150° vertical (at 5:1)
	Response Time	8ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit+2-bit FRC)
	Light Source	Long life, 50000 hrs. (typ.)
	Brightness	280cd/m ² (typ.)
	Panel Surface	Anti-glare (3H)
VIDEO INPUT	Analogue	RGB analogue (0.7 Vp-p, 75 ohm)
	Frequency	Fh: 30 ~ 82kHz, Fv: 50 ~ 85Hz
	Synchronisation	H/V separate (TTL)
COMPATIBILITY	PC	VGA up to 1280 x 1024 non-interlaced (max. 75Hz)
	Mac [®] 1	Power Mac™ up to 1280 x 1024 non-interlaced (max. 75Hz)
CONNECTOR	Analogue	15-pin mini D-Sub (attached cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin AC plug (CEE22)
POWER	Voltage	AC 100 – 240V, 50/60Hz (auto switch), internal power supply
	Consumption	35 watt (typ.) <1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, up 20°
	Height Adjustment	0 ~ 100mm
AUDIO	Speakers	2 x 1-watt
	Amplifier	1-watt @ THD < 8%
CONTROLS	Basic	Power, menu [1], down, up, select [2], mute
	OSD	Auto image adjust, contrast, brightness, audio (volume, mute), ViewMatch [®] colour adjust (sRGB, 9300K, 6500K, 5400K, User-RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITIONS	Temperature	0°C – 40°C
	Humidity	10% – 90% (non-condensation)
DIMENSIONS	W x H x D mm	423 x 434 – 534 x 221 (with stand) 423 x 381 x 52 (without stand)
WEIGHT	Net	5.2kg (with stand) 4kg (without stand)
REGULATIONS		TCO'03, TÜV/GS, TÜV/ERGO, ISO13406-2 (pixel failure class II), CE, CB, UL, cUL, FCC-B, Energy Star [®] , GOST-R, NOM, Argentina-TÜV-S, SASO, BSMI, CCC, PSB, C-TICK, ICES 003, Korea (MIC)
POWER MANAGEMENT		Meets TCO'03 and Energy Star [®] standards
SECURITY		Kensington [®] security port
WALL MOUNT		VESA [®] FPDm 100mm x 100mm
PACKAGE CONTENTS		LCD monitor, power cable, VGA cable, audio cable, Quick Start Guide, ViewSonic Wizard CD (User Guide/drivers)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 056/85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)9 5406 4070
Tel: +34 (0) 91 63 05 339
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter.