

Pure LCD monitor enjoyment

Latest state-of-the-art features make the ViewSonic VP720 perfect for all graphics professionals, gaming developers and corporate executives. ClearMotiv™ technology delivers an ULTRA-FAST 4MS VIDEO RESPONSE TIME that enables high-quality full motion video playback and also makes the monitor ideal for video editing applications. Analogue and digital inputs are available for various connectivity options. This multimedia enhanced model boasts a full 17" viewable screen with a high-definition 1280 x 1024 resolution as well as built-in stereo speakers for maximum convenience. In addition, the VP720 allows for the adjustment of HEIGHT, PIVOT AND TILT to give it an ergonomic edge.

VP720

**ERGONOMIC 17" LCD MONITOR
WITH ULTRA-FAST 4MS VIDEO RESPONSE**

It's not just another professional LCD. It's a ViewSonic.



VP720 - FLEXIBLE 17" LCD MONITOR

- > **Adaptable advanced ergonomics - Height adjustable, pivot² and tilt**
Provides the most comfortable viewing position for the user, enabling increased productivity.
- > **OPTISYNC[®] multiple analogue/digital inputs**
Includes DVI-D and analogue inputs providing the IT department with maximum connectivity to multiple sources.
- > **Multimedia enhanced**
Save workspace and enjoy rich stereo sound with built-in stereo speakers.
- > **TCO'03 and ENERGY qualified**
Providing the latest certification to ensure IT departments provide the highest standards of personal wellbeing for users and ensuring corporate environmental responsibilities are met.
- > **ClearMotiv™ 4ms video response time**
Ultra-fast 4ms video response time enables digital broadcast-quality full motion video.
- > **sRGB compliant**
Achieves accurate colour match between screen and printer.
- > **Thin Edge™ - Ideal for multi monitor set-ups**
Display continuous images in multiple panel set-ups. Designed for minimal bezel gaps between panels
- > **Full 17" - Viewable screen with 1280 x 1024 resolution**



VIEWSONIC
PRODUCTS, PROGRAMS,
AND SERVICES

ViewSonic 
the choice of professionals

VP720

ERGONOMIC 17" LCD MONITOR WITH ULTRA-FAST 4MS VIDEO RESPONSE



LCD	Type	17" TN colour TFT active matrix SXGA LCD
	Display Area	33.8cm horizontal x 27.0cm vertical, 43.2cm diagonal
	Pixel Pitch	0.264mm
	Optimum Resolution	1280 x 1024
	Bandwidth	135MHz
	Contrast Ratio	500:1 (typ.)
	Viewing Angle	140° horizontal, 130° vertical (at 10:1) 170° horizontal, 170° vertical (at 5:1)
	Response Time	4ms (Grey-to-Grey), 8ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit+2-bit FRC)
	Brightness	280cd/m ²
	Panel Surface	Anti-glare
VIDEO INPUT	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohm)
	Digital	DVI-D (TMDS, 100 ohm)
	Frequency	F _H : 24 – 82kHz, F _V : 50 – 85Hz
	Synchronisation	H/V separate (TTL), composite, sync on green
COMPATIBILITY	PC	VGA up to 1280 x 1024 non-interlaced (max. 60Hz)
	Mac®	Power Mac™ up to 1280 x 1024 non-interlaced (max. 60Hz)
CONNECTOR	Analogue	15-pin mini D-Sub (detachable cable)
	Digital	24-pin DVI-D (detachable cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin (CEE22)
AUDIO	Speakers	2 x 1 watt
POWER	Voltage	AC 100 – 240V, 50/60Hz (auto switch), internal power supply
	Consumption	<45 watt (max.), ≤1 watt in power save mode
ERGONOMICS	Tilt	Down 5°, Up 20°
	Pivot	0°~90°
	Height Adjustment	0~100mm
CONTROLS	Basic	Power on/off, menu [1], up, down, select [2]
	OSD	Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), Audio adjust (volume, mute), colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K, 5000K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
OPERATING CONDITIONS	Temperature	0°C - 40°C
	Humidity	10% - 90% (non-condensation)
DIMENSIONS	(W x H x D mm)	376 x 463 x 229 (with stand) 376 x 320 x 68 (without stand)
WEIGHT	Net	5.45kg (with stand), 3.7kg (without stand)
REGULATIONS		TCO'03, TÜV/GS, TÜV/ERGO, CE, CB, UL, cUL, FCC-B (ICES), ICES-003B, ENERGY, Energy Star, NOM, ISO13406-2 (pixel failure class II), GOST-R (+Hygienic), BSMI, CCC, PSB, C-TICK, TÜV-S, KTL/MIC, SASO, WEEE, RoHS
POWER MANAGEMENT		Meets TCO'03, ENERGY and Energy Star standards
SECURITY		Kensington® security port
WALL MOUNT		VESA FPMPMI 100mm x 100mm
PACKAGE CONTENT		LCD Monitor, power cable, 15-pin VGA video cable, DVI cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers)
WARRANTY		Please see: www.viewsoniceurope.com/UK/Support/warranty.htm



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbannières
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 056/85 26 27
Tel: +45 70 22 11 71
Tel: +358 (0)9 5406 4070
Tel: +34 (0) 91 63 05 339
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ May require optional Mac adapter

² Pivot software optional available.

³ Mounting options available from 3rd party suppliers.

Copyright © 2006, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VP720-05/06-UK