

## Rich features to boost productivity

The 19" big-screen LCD monitor VP920 features HEIGHT, PIVOT AND SWIVEL adjustment for optimal ergonomic settings. Its ultra-slim bezel design enables multi-display configurations for enhanced productivity and fast decision-making by financial traders, corporate planners and engineers. ClearMotiv™ technology delivers an ULTRA-FAST 4MS VIDEO RESPONSE TIME that is perfect for working with intensive graphics applications or fast-paced video games. Additionally this LCD monitor includes analogue and digital inputs for VARIOUS CONNECTIVITY OPTIONS. The VP920 is also multimedia enhanced, including integrated speakers for maximum entertainment value.

# VP920

**ERGONOMIC 19" LCD MONITOR  
WITH ULTRA-FAST 4MS VIDEO RESPONSE**

**It's not just another professional LCD. It's a ViewSonic.**

### VP920 - FLEXIBLE 19" LCD MONITOR

- > **Adaptable advanced ergonomics - Height adjustable, pivot<sup>2</sup> and tilt**  
Provides the most comfortable viewing position for the user, enabling increased productivity.
- > **OPTISYNC® multiple analogue/digital inputs**  
Includes DVI-D and analogue inputs providing the IT department with maximum connectivity to multiple sources.
- > **Multimedia enhanced**  
Save workspace and enjoy rich stereo sound with built-in stereo speakers.
- > **TCO'03 and ENERGY qualified**  
Providing the latest certification to ensure IT departments provide the highest standards of personal well-being for users and ensuring corporate environmental responsibilities are met.
- > **ClearMotiv™ 4ms video response time**  
Ultra-fast 4ms video response time enables digital broadcast-quality full motion video.
- > **sRGB compliant**  
Achieves accurate colour match between screen and printer.
- > **Thin Edge™ - Ideal for multi monitor set-ups**  
Display continuous images in multiple panel set-ups. Designed for minimal bezel gaps between panels
- > **Full 19" - Viewable screen with 1280 x 1024 resolution**



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES

**ViewSonic**   
the choice of professionals

# VP920

## ERGONOMIC 19" LCD MONITOR WITH ULTRA-FAST 4MS VIDEO RESPONSE



<b>LCD</b>	Type	19" TN colour TFT active matrix SXGA LCD
	Display Area	37.6cm horizontal x 30.1cm vertical, 48.3cm diagonal
	Pixel Pitch	0.294mm
	Optimum Resolution	1280 x 1024
	Bandwidth	135MHz
	Contrast Ratio	500:1 (typ.)
	Viewing Angle	140° horizontal, 130° vertical (at 10:1) 160° horizontal, 140° vertical (at 5:1)
	Response Time	4ms (Grey-to-Grey), 8ms (off-on-off) (typ.)
	Colour Support	16.2M colours (6-bit+2-bit FRC)
	Brightness	250cd/m <sup>2</sup> (typ.)
	Panel Surface	Anti-glare
<b>VIDEO INPUT</b>	Analogue	RGB analogue (0.7/1.0 Vp-p, 75 ohms)
	Digital	DVI-D (TMDS, 100 ohms)
	Frequency	F <sub>H</sub> : 24 - 82kHz, f <sub>v</sub> : 50 - 85Hz
	Synchronisation	H/V separated (TTL), composite, sync on green
<b>COMPATIBILITY</b>	PC	VGA up to 1280 x 1024 non-interlaced (max. 60Hz)
	Mac <sup>®</sup>	Power Mac <sup>™</sup> up to 1280 x 1024 non-interlaced (max. 60Hz)
<b>CONNECTOR</b>	Analogue	15-pin mini D-Sub (detachable cable)
	Digital	24-pin DVI-D (detachable cable)
	Audio	3.5mm stereo audio line-in
	Power	3-pin (CEE22)
<b>AUDIO</b>	Speakers	2 x 1 watt
<b>POWER</b>	Voltage	AC 100 - 240V, 50/60Hz (auto switch), internal power supply
	Consumption	<45 watt (max.), ≤1 watt in power save mode
<b>ERGONOMICS</b>	Tilt	Down 5°, Up 20°
	Pivot	0°-90°
	Height Adjustment	0~100mm
<b>CONTROLS</b>	Basic	Power on/off, menu [1], up, down, select [2]
	OSD	Auto image adjust, contrast, brightness, input select (D-sub, DVI-D), Audio adjust (volume, mute), colour adjust (sRGB, 9300K, 7500K, 6500K, 5400K, 5000K, user RGB), information (resolution, H/V frequency, pixel clock, model number, serial number, website), manual image adjust (H/V position, H size, fine tune, sharpness), setup menu (language, resolution notice, OSD position, OSD timeout, OSD background), OSD/power lock, memory recall
<b>OPERATING-CONDITIONS</b>	Temperature	0°C - 40°C
	Humidity	10% - 90% (non-condensing)
<b>DIMENSIONS</b>	(W x H x D mm)	416 x 479 x 238 (with stand) 416 x 352 x 70 (without stand)
<b>WEIGHT</b>	Net	6.3kg (with stand), 4.6kg (without stand)
<b>REGULATIONS</b>		TCO'03, TÜV/GS, TÜV/ERGO, CE, CB, UL, cUL, FCC-B (ICES), ICES-003B, ENERGY, Energy Star, NOM, ISO13406-2 (pixel failure class II), GOST-R (+Hygienic), BSMI, CCC, PSB, C-TICK, TÜV-S, KTL/MIC, SASO, WEEE, RoHS
<b>POWER MANAGEMENT</b>		Meets TCO'03, ENERGY and Energy Star standards
<b>SECURITY</b>		Kensington <sup>®</sup> security port
<b>WALL MOUNT</b>		VESA FPM/PMI 100mm x 100mm
<b>PACKAGE CONTENTS</b>		LCD Monitor, power cable, 15-pin VGA video cable, DVI cable, audio cable, Quick Start Guide, ViewSonic Wizard CD-ROM (User Guide/drivers)
<b>WARRANTY</b>		Please see: <a href="http://www.viewsoniceurope.com/UK/Support/warranty.htm">www.viewsoniceurope.com/UK/Support/warranty.htm</a>



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

**ViewSonic Europe Limited/UK**  
ViewSonic House  
Fleming Way, Crawley  
West Sussex, RH10 9GA  
United Kingdom

Tel: +44 (0) 12 93 64 39 00  
Fax: +44 (0) 12 93 64 39 10

**ViewSonic Germany**  
Hanns-Martin-Schleyer-Straße 18A  
47877 Willich  
Germany

Tel: +49 (0) 21 54 91 88 0  
Fax: +49 (0) 21 54 91 88 10

**ViewSonic France**  
Parc des Barbannières  
1 allée des Bas Tilliers  
92230 Gennevilliers  
France

Tel: +33 (0) 1 41 47 49 00  
Fax: +33 (0) 1 41 47 49 10

**ViewSonic Corporation**  
381 Brea Canyon Road  
Walnut  
California 91789-0708  
USA

Tel: +1 909 869 7976  
Fax: +1 909 869 7958

**ViewSonic Benelux**  
**ViewSonic Denmark**  
**ViewSonic Finland**  
**ViewSonic Italy**  
**ViewSonic MEA**  
**ViewSonic Norway**  
**ViewSonic Spain**  
**ViewSonic Sweden**

Tel: +32 056/85 26 27  
Tel: +45 70 22 11 71  
Tel: +358 (0)9 5406 4070  
Tel: +34 (0) 91 63 05 339  
Tel: +971 (0) 4 88 11 871  
Tel: +47 (0) 22 88 17 60  
Tel: +34 (0) 91 63 05 339  
Tel: +46 (0) 8 50 71 30 00

<sup>1</sup> May require optional Mac adapter

<sup>2</sup> Pivot software optional available.

<sup>3</sup> Mounting options available from 3rd party suppliers.

Copyright © 2005, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS VP920-12/05-UK