



ViewSonic  | Business

ViewBoard IFP63 Series 4K PCAP Touch EDLA Certified Interactive Display

Collaborate with Security and Precision

The ViewSonic® ViewBoard® IFP63 Series is a 4K UHD interactive display built for secure, high-performance collaboration in enterprise and higher education. With ultra-responsive 50-point PCAP touch and Write Away™ technology, it delivers a seamless pen-on-paper writing experience. Powered by Android 15 and EDLA-certified, it ensures ongoing Android security updates and access to Google Play apps on a future-ready platform. An octa-core processor with 16/32GB RAM supports demanding workflows, while NFC tap-to-sign-in simplifies shared use. As part of ViewSonic Business Solutions, it includes Manager for remote device management, AirSync for wireless casting, and TeamOne for real-time collaboration. Certified EPEAT Gold and EEI Level F, it also features built-in sensors that activate energy-saving modes for efficient power use.



Smooth, Accurate Writing

50-point PCAP touch with 1 mm accuracy delivers zero-lag, precise multi-user writing.



Future-Ready Performance

Android 15 with upgrade support, octa-core CPU, and up to 32GB RAM ensure smooth, reliable performance.



Enterprise-Grade Security

Stay protected with the latest Android security patches, Google Play Protect, encryption, and 2FA.



Simplified Remote Management

Control and maintain the interactive display remotely via Manager's centralized web dashboard.



Built-in Google Services

Seamlessly collaborate with Google Workspace apps and Google Play access.



Eco-Minded Design

EPEAT Gold and ENERGY STAR certified, consuming up to 24% less energy than the previous generation.



Explore the ViewBoard IFP63 Series: <https://vsonic.global/IFP63>

Specifications and availability are subject to change without notice.
Corporate names and trademarks stated herein are the property of their respective companies.
Copyright © 2025, ViewSonic Corporation. All rights reserved.



IFP63 Series

Model		IFP6563	IFP7563	IFP8663
DISPLAY	Panel Size	65"	75"	86"
	Type/Tech	TFT LCD module with DLED backlight, ADS		
	Display Area (mm)	1428.48(H) x 803.52(V) (64.5" diagonal)	1650.24 (H) x 928.26 (V) (74.5" diagonal)	1895.04 (H) x 1065.96 (V) (85.6"diagonal)
	Aspect Ratio	16:9		
	Native Resolution	UHD 3840x2160(Pixels)		
	Colors	1.07G colors (8-bit+FRC)		
	Brightness	450 nits (typ.)		
	Backlight Life	50,000 Hours		
	Contrast Ratio	5000:1		
	Response Time	6.5ms	6.5ms	8ms
	Viewing Angles	H = 178, V = 178 typ.		
	Backlight Life	50,000 Hours		
	Surface Treatment	Hardness: Pencil Hardness 9H with AG+AF+Anti-bacteria		
	Haze	25%		
	Bezel (L/R/T/B)	31.4/31.4/38.9/64.8 mm	31.1/31.1/38.6/63.5 mm	32.5/32.5/39.7/64.8 mm
Orientation	Landscape			
PLATFORM	Processor	Octa-Core CPU		
	RAM	16GB / 32GB		
	Storage	128GB		
TOUCH	Type/Tech	PCAP		
	Touch Resolution	32767 x 32767		
	Touch Point	Windows: 50 Android: 50		
INPUT	HDMI-IN	x4 (FRONT x1: HDMI 2.1 support CEC; REAR x3: HDMI 2.1, HDMI 1 support CEC, ARC; HDMI 2, 3 support CEC)		
	DisplayPort	x1 (DP1.2)		
	Audio 3.5mm	x1		
	RS232	x1		
	SD/SDHC	MicroSD card slot x1		
	OPS	OPS slot x1		
OUTPUT	HDMI-OUT	x1 (4K@60Hz)		
	Audio 3.5mm	x1 (Line out)		
	SPDIF	x1 (Optical)		
LAN	RJ45	x2 (Speed: 10/100/1000Mbps, WOL supported, ProAV vendor & ViewSonic protocol supported)		
USB	Type A	x5 (REAR x1 (USB 2.0 support OTG) ; REAR x2 (USB 3.2 Gen 1) ; FRONT x2 (USB 3.2 Gen 1))		
	Type B	x3 (FRONT x1 (USB 2.0); REAR x2 (TOUCH 1: USB 3.0; TOUCH 2: USB 2.0))		
	Type C	FRONT x1 (DP 1.2, touch, 100M ethernet, USB 3.2 Gen 1, smart USB 2.0, PD 65W) REAR x1 (DP 1.2, touch, 100M ethernet, USB 3.2 Gen 1, smart USB 2.0, PD 100W) TOP x1 (USB 3.2 Gen 1 + PD15W to support Camera mounting)		
MICROPHONE	Built-in 8 Array-Microphone			
SPEAKER	20W x 2 + 20W x 1 (Subwoofer)			
ENVIRONMENTAL SENSOR	Temperature Sensor x1, Humidity Sensor x1, eCO2 Sensor x1, VOCs Sensor x1, PM2.5 Sensor x1			
TOP CAMERA PLATE	Yes			
COMPATIBILITY	HDMI	3840X2160 @60Hz		
EMBEDDED OS	Android Version	Android 15		
POWER	Voltage	100-240VAC +/- 10% Wide Range		
	Consumption	88.5W (Energy Star)/ Off: <0.5W	101.1W (Energy Star)/ Off: <0.5W	121.1W (Energy Star)/ Off: <0.5W
ERGONOMICS	Wall Mount (VESA*)	600x400	800x400	800x600
OPERATING CONDITIONS	Temperature (°C)	0°C - 40°C(working)		
	Humidity	20% - 80% RH Non-Condensing(working)		
DIMENSIONS (W x H x D)	Physical (inch/mm)	58.8 x 35.8 x 3.1in/ 1493.3 x 909.3 x 78.8mm	67.5 x 40.7 x 3.1in/ 1714.3 x 1032.4 x 79.1mm	77.2 x 46.2 x 3.1in/ 1961.9 x 1172.5 x 79.5mm
	Packaging (inch/mm)	64.1 x 40.9 x 7.3in/ 1628 x 1040 x 185mm	73.3 x 45.2 x 8.9in/ 1863 x 1148 x 225mm	87 x 50.8 x 8.9in/ 2110 x 1291 x 225mm
WEIGHT	Net (lb / kg)	92.8lb / 42.1kg	123.7lb/ 56.1kg	143.5lb/ 65.1kg
	Gross (lb / kg)	110.9lb/ 50.3kg	152.1lb/ 69kg	185.6lb/ 84.2kg
REGULATIONS	cTUVus, FCC, EPEAT, CE, CB, BSMI, NCC, RoHS DoC, WEEE, ErP, Flicker Free, Low Blue Light			
ENERGY STAR VERSION	ES 8.0			
EEI RATING	F			
PACKAGE CONTENTS	1. 3m power cord by ship area 2. Type C cable 1.8m(USB-IF certified) 3. 3m touch USB cable (USB 2.0) 4. Touch pen x 2 (VB-PEN-101-2C) 5. RS232 adapter	6. Quick Start Guide 7. Clamp x 5 8. Camera Plate 9. Screw x 10 (camera 2+4, wall mount 4) 10. HDMI cable 3m (HDMI LA certified)	11. Remote control 12. AAA Battery x 2 13. Compliance statement	
COMPATIBLE ACCESSORIES	Slot-in PC	VPC3X Series/ VPCF5-2A Series/ VPCF5 Series/ VPC-A31-O1		
	WiFi Module	VB-WIFI-001, VB-WIFI-005		
	Camera	VB-CAM-002, VB-CAM-201		
	Stand/ Trolley Cart	VB-STND-002, VB-STND-003, VB-STND-004, VB-STND-008, VB-STND-009		