VA2413wm

24" (23.6" VIEWABLE) WIDESCREEN LCD

WITH 16,000:1 DYNAMIC CONTRAST RATIO

Environmentally friendly, 1920 × 1080 LCD

ViewSonic's 24" (23.6" viewable) VA2413wm 16:9 widescreen LCD delivers 1920 × 1080 performance and ultra-high 16,000:1 dynamic contrast ratio for unsurpassed HD content on your desktop. It's ideal for business applications where blur-free motion, crisp detail and precise images are critical. The aspect ratio adjustment ensures that even your 4:3 images are displayed without any stretching or distorion. This display is multimedia ready with hidden speakers. The VA2413wm is environmentally friendly with TCO'03 certification and Eco-mode that automatically reduces power consumption and can extend backlight life. The VA2413wm is ideal for corporate use where an eco-friendly, high-performance LCD can enhance your productivity.

High-performance for your desktop

- > Full HD resolution (1920x1080) with 16:9 aspect ratio Perfect for Full HD Games and Movies, playing and editing, or for viewing massive spreadsheets or multiple applications simultaneously.
- > 16,000 :1 dynamic contast ratio Provides darker black levels and better overall front-of-screen performance.
- > ECO Mode (3 Types)
 - Environmentally-friendly Eco-mode reduces power consumption and extends backlight life.
 - Standard Mode Optimized Mode: 25% Power Saving Conserve Mode: 40% Power Saving
- > Aspect ratio function to adjust 4:3 and full screen image Eliminates image distortion by maintaining correct image proportions for both widescreen and native 4:3 content.
- > Invisible 2w stereo speakers Multimedia ready
- > ENERGY STAR[®] and TCO'03 qualified







VA2413wm



23.6" wide Color TFT Active Matrix LCD 16:9 aspect ratio

521 (mm) × 293 (mm) / 20.5 (in) × 11.5 (in)

Model No.VS12302

24" (23.6" viewable) 16:9 widescreen LCD with Full HD 1080p resolution

Display Area

Size







	Display / lica	321 (http://2003 (http://2003 (http://	
	Optimum Resolution	1920 × 1080 WUXGA (Full HP)	
	Brightness	300 cd/m² (typ.)	
	Contrast Ratio	1000:1 (typ.) ; 16000:1 dynamic	
	Viewing Angles	170° (H), 160° (V) at CR≧10 / 170° (H), 170° (V) at CR≧5	
	Response Time	5ms (on/off)	
	Pixel Pitch	0.2715mm (H) × 0.2715mm (V)	
	Panel Surface	Anti-Glare, Hard coating (3H)	
	Light Source	50,000 hrs (typ.)	
	Color Support	16.7 M (6-bits + Hi FRC)	
INPUT	Analog	RGB Analog (75 ohms, 0.7 Vp-p)	
	Sync	Separate Sync	
	Frequency	Fh: 22-82kHz, Fv: 50-75Hz	
COMPATIBILITY	PC	VGA up to 1920 × 1080 non-interlaced	
	Mac **	Power Mac, up to 1920 × 1080	
CONNECTOR	Analog	15 pin mini D-sub × 1	
	Audio	3.5 mm Audio line-in	
	Power	3-pin AC plug (CEE22)	
AUDIO	Speaker (W)	2×2 watt	
POWER	Voltage	AC 100-240V (Universal); 50 / 60Hz (Switch)	
	Consumption (W)	47 (Max)	
	Eco Mode	Standard 45W / Optimize 31W / Conserve 26W	
	Save mode (W)	≦1W	
ERGONOMICS	Tilt	20° ~ -5°	
CONTROLS	Basic	[1], [2], Power, Down, Up	
	OnView	Auto Image Adjust, Contrast/Brightness, Audio Adjust (Volume, mute),	
		Color Adjust (sRGB, 9300K, 7500K, 6500K, 5000K, User Color [R, G, B]),	
		Information, Manual Image Adjust (H/V Position, Horizontal Size, Fine	
		Tune, Sharpness, Dynamic Contrast, Aspect Ratio, ECO Mode), Setup	
		Menu (Language, Resolution Notice, OSD Position, OSD Timeout, OSD	
		Background, Sleep), Memory Recall	
OPERATING	Temperature	5 - 35°C (41 - 95°F)	
CONDITIONS	Humidity	20 - 80% (Non condensed)	
DIMENSIONS	Physical (w/ stand)	564mm × 417mm × 261mm	
(WxHxD)	Physical (w/o stand)	564mm × 335mm × 67mm	
WEIGHT Net		5.3 kg	
	Gross weight	6.8 kg	
REGULATIONS		CB, TCO'03, WEEE, RoHS, UL/cUL, FCC-B, IRAM, NOM, Energy Star,	
		NEMKO/ERGO, CE, Ukraine, GOST-R+Hygienic, SASO, BSMI, PSB, C-TICK,	
		MIC, VCCI, CCC	
WALL MOUNT		VESA 100mm × 100mm	
POWER MANAGEMENT		TCO'03, ENERGY STAR	
PACKAGE CONTENTS		ViewSerie VA2412 and 2 LCD, VCA apple Bewer public Quiel Start	
PACKAGE CONTE	ENTS	ViewSonic VA2413wm-2 LCD, VGA cable, Power cable, Quick Start	



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.

ViewSonic	Europe	Limited/UK

Riverside House 7th Floor 2a Southwark Bridge Road London, SE1 9HA United Kingdom Tel: +44 (0) 207 921 2200 Fax: +44 (0) 207 921 2201 ViewSonic Germany Hanns-Martin-Schleyer-Straße 18A 47877 Willich Germany Tel: +49 (0) 21 54 91 88 0 Fax: +49 (0) 21 54 91 88 10

ViewSonic France Parc des Barbanniers 1 allée des Bas Tilliers 92230 Gennevilliers France Tel: +33 (0) 1 41 47 49 00 Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation 381 Brea Canyon Road Walnut California 91789-0708 USA Tel: +1 909 869 7976 Fax: +1 909 869 7958
 ViewSonic Benelux
 Tel: +31 (0)20 491 9254

 ViewSonic Demmark
 Tel: +45 70 22 11 71

 ViewSonic Finland
 Tel: +358 (0)20 7120 860

 ViewSonic MEA
 Tel: +971 (0) 4 88 11 871

 ViewSonic Norway
 Tel: +474 (0) 22 88 17 60

 ViewSonic Spain
 Tel: +34 (0) 91 63 05 339

 ViewSonic Sweden
 Tel: +46 (0) 8 50 71 30 00

*Requires SRS Audio Sandbox Software to be installed. **Adapter may be required. Copyright © 2008 ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Errors & omissions excepted. Corporate names and trademarks stated herein are the property of their respective companies. VA2413wm 01/09-UK

For more product information, visit us on the web at viewsoniceurope.com