

# Boosting your work efficiency


VG2433-LED



The ViewSonic® VG2433-LED is a 23.6" display ideal for demanding business professionals. With a native 1920x1080 resolution, the VG2433-LED delivers vibrant images and crisp text. Users will also find comfort in the fully ergonomic height adjust, swivel, and tilt features. Equipped with a VESA-mountable design, the display can be mounted on a wall or any VESA-compliant monitor stand. The VG2433-LED also saves up to 50% in energy usage with its efficient LED backlight. With ViewSonic's industry-best pixel performance guarantee, and a 3-year warranty, the VG2433-LED provides users with peace of mind.

## **Ergonomic design for comfortable working environments**

Users can reduce eyestrain and physical fatigue by adjusting the monitor to create their own most comfortable work environment. The VG2433-LED is designed to maximize comfort and productivity with advanced ergonomic technology. This fully ergonomic design offers over 10cm of height adjustment, 360° swivel, and a tilt angle from -5° to 25°.



### Full HD resolution for superb pixel performance

Experience the most amazing clarity and detail for any of your computer applications, Microsoft Office Suite operations, or for enjoying the latest multimedia entertainment. The VG2433-LED features full HD 1920x1080 resolution to ensure excellent pixel-by-pixel image performance. Additionally, this 16:9 large screen allows the user to operate multiple windows side by side, thus facilitating a more efficient work environment.



### MEGA Dynamic Contrast Ratio delivers sharp and crisp images

The superior dynamic contrast ratio of 20,000,000:1 delivers a broader range of grayscale, with darker blacks and brighter whites, to ensure all images displayed are rich and detailed. An extremely fast 5ms response time results in crisp and clear video performance. Experience digital broadcast-quality, full-motion video with razor-sharp images that never blur.



### Eco Mode saves energy and lowers total cost of ownership

ViewSonic's proprietary Eco Mode function is built into all LED displays to provide setting options to "Optimize" (75%) and "Conserve" (50%). Both modes reduce display brightness and conserve up to 40% more energy. Eco Mode adjusts brightness and improves visibility, especially in low ambient light, to reduce eye fatigue and prolong display lamp lifetime. With Eco Mode, replacement expenditures are reduced while practicing eco-friendliness.



### sRGB delivers the most accurate color performance

Accurate and consistent color performance is essential for professionals in graphic design, video editing, and other multimedia related environments. With built-in sRGB color correction technology, the VG2433-LED reproduces images in their original and authentic colors.



## Rendimiento del pixel garantizado + Garantía limitada a 3 años

Uno de los aspectos que convierten a ViewSonic en líder de mercado de soluciones de visualización es su dedicación a la calidad. ViewSonic se compromete a utilizar los paneles de más alta calidad y ofrece un rendimiento de pixel líder de la industria.

Rendimiento del pixel	Monitores LED
<b>ISO9241-3: 2008 Standard</b>	<b>2 Brillo 2 Oscuro 5 Total</b>
<b>Garantía ViewSonic Pixel</b>	<b>2 Brillo 2 Oscuro 3 Total</b>

## Technical Specifications

---

### LCD

Ratio de contraste	1,000:1
Ángulos de visión	170° / 160°
Área de visualización	23.6" Wide
Resolución óptima	1920 x 1080
Tiempo de respuesta	5 ms
Superficie del panel	Anti-glare Type, 3H Hardness
Brillo	300 cd / m2
Relación de contraste dinámico	20,000,000:1
Retroiluminación	White-light LED
Vida útil de retroiluminación	30,000 hrs (min.)

### COLORS

Black

### COMPATIBILIDAD

PC	VGA up to 1920 x 1080 non-interlaced
Mac®	MAC up to 1280 x 1024

### Dimensiones

Embalaje	581mm (W) x 483 mm (H) x187 mm (D) 22.87" (W) x 19.01" (H) x7.36" (D)
Físicas con la base	566mm (W) x382.4 mm (H) x 204.3 mm (D)  22.28" (W) x 15.06" (H) x8.04" (D)
Físicas sin la base	566.0mm (W) x343.2 mm (H) x 51mm (D) 22.28" (W) x 13.51" (H) x2.01" (D)

### Entrada de vídeo

Analógico	RGB Analog (75Ω, 0.7 / 1.0 Vp-p)
-----------	----------------------------------

Frecuencia	Fh□24 - 82kHz□Fv□50 - 75Hz
Sincronización	Separate Sync/ Composite Sync/ SOG
Digital	DVI (TMDS□100 ohms)

---

**Conectividad**

Audio	N/A
Alimentación	Internal Power Board , 3-pin plug (CEE22) *1
USB	N/A

---

**Alimentación**

Conservación	15W (typ.)
Optimización	18W (typ.)
Voltaje	AC 100 - 240V (Universal)□50 / 60Hz
Consumo	22W (typ.)

---

**Peso**

Bruto	10.27 lbs (4.66 Kg)
Neto con la base	7.1 lbs (3.22 Kg)
Neto sin la base	14.82 lbs (6.72 Kg)

---

**VESA® MONTAJE**

100mm \* 100mm

---

**GESTIÓN DE ENERGÍA**

Eco Mode

---

**ERGONOMÍA**

Ajuste de altura	0-100mm
Rotación	90°
Inclinación	25%° ~ -5°
Giratoria	360°

---

**CONDICIONES DE FUNCIONAMIENTO**

Humedad	10% to 90% (no condensation)
Temperatura	32° F to 104° F (0° C to 40° C)

---

**AUDIO OUT**

Speakers	N/A
----------	-----

---

**PACKAGE CONTENTS**

Power Cable \*1□D-Sub\*1□Quick Start Guide \*1,  
ViewSonic CD Wizard \*1

---

## **ViewSonic® Limited Warranty**

---

ViewSonic provides customers with the security of a manufacturers warranty against defected products. The type and duration of the applicable warranty service varies by product type, country of purchase and can also vary on an individual basis according to customer requirements agreed at time of purchase. The warranty will expire after the end of the warranty period.

---

For more product information, visit us at **[www.viewsoniceurope.com](http://www.viewsoniceurope.com)**

All rights reserved by ViewSonic Corporation. All other Corporate names and trademarks are the property of their respective companies. E&EO. All prices and specifications are subject to change without written notice. Images are for illustrative purpose only. Terms & Conditions Apply.