



ViewSonic  | Business

ViewSonic® Ultrawide ViewBoard® Interactive Displays

Make Space for Collaboration

Equipped with multi-touch functionality and a 21:9 aspect ratio, ViewSonic® Ultrawide ViewBoard® Interactive Displays foster interactive collaboration and boost productivity. Available in 92" and 105" sizes with 5K resolution, they integrate seamlessly with Microsoft Teams Rooms for streamlined meetings.

Microsoft Teams Rooms Front Row Optimized

Show attendees, content, and chat on an expansive 21:9 display, enhancing hybrid meeting inclusivity and collaboration.

Ultra-responsive Touchscreen

Supports up to 50-point touch, letting multiple users write or draw with styluses or fingers for better collaboration.

Crystal-clear Communication

Empower hybrid meetings with the integrated, responsive 8-mic array and speakers, ensuring crystal-clear audio for all.

Incredible 5K Ultra HD Resolution

Deliver sharp, detailed visuals with native 5120 x 2160 resolution for clear viewing across the entire room.

Multi-device Wireless Screen Sharing

Share screens from up to 9 devices wirelessly via vCast for seamless communication and collaboration in meetings.

USB-C One Cable Solution

With dual USB-C ports, connect your laptop to transfer data, charge, broadcast multimedia, and access Ethernet—all with one cable.

Explore the IFPUW Ultrawide Series: <https://vsonic.global/IFPUW>

Specifications and availability are subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. Copyright © 2024, ViewSonic Corporation. All rights reserved.



Spec Table

		IFP92UW	IFP105UW
DISPLAY	Panel Size	92"	105"
	Panel Type	TFT LCD Module with DLED Backlight	
	Display Area (mm)	2141.952(H) x 903.636(V) (91.52" diagonal)	2449.92(H) x 1033.56 (V) (104.6" diagonal)
	Aspect Ratio	21:9	
	Resolution	WUHD 5120x2160 (Pixels)	
	Colors	1.07G colors	1.07B colors
	Brightness	500nits (typ.)	400nits (typ.)
	Contrast Ratio	5000:1	
	Response Time	<6.5ms	6.5ms
	Viewing Angles	H = 178, V = 178 (Typ.)	
	Backlight Life	50,000hrs	30,000hrs
	Surface Treatment	Panel Hard Coating 3H Glass Anti-Glare 7H	
Bezel	19.48/19.48/29.78/41.18 mm	19.5/19.5/29.8/41.2 mm	
Orientation	Landscape		
PLATFORM	Embedded OS	Android 13	
	Processor	Octa-Core CPU	
	RAM	8GB	
	Storage	128GB eMMC	
TOUCH	Type	IR	
	Touch Resolution	32767 x 32767	
	Touch Point	Windows: 50 points ; Android: 32 points	Windows: 40 points ; Android: 20 points
	Point of Writing	5-point with -2mm pen tip 10-point with -8mm pen tip	10
	Response Time	≤5ms	
	Scan rate	≥200HZ	
	Accuracy Size	±1mm for 90% of screen area ±1.5mm around 10% of the edges	90% area +/- 1mm
	Pen Tips Size	2mm/8mm	
INPUT	HDMI-IN	4 (HDMI2.1*1 + HDMI 2.0*3)	
	DisplayPort	1	
	Audio	1	
	RS232	1	
	OPS	1 (OPS Slot 80pin)	
	WiFi	1 (Module Slot)	
OUTPUT	HDMI	1	
	Audio	1	
	SPDIF	1	
LAN	RJ45	2 (Android & PC 10M/100M/1000Mbps)	
USB	Type-A	7 (USB2.0*1, USB3.2 Gen 1*6)	
	Type-B	3 (USB2.0)	
	Type-C	FRONT x1 (1*PD15W + DP1.2 + Data + 10M/100M sharing, USB 3.2 Gen 1) REAR x1 [1*PD65W(65W with OPS, 100W without OPS) + DP1.2 + Data + 10M/100M sharing, USB 2.0]	
MICROPHONE ARRAY	-	Built-in 8 Array Microphone	
SPEAKERS	-	20W x 2 + 20W x 1 subwoofer	16W x 2 + 15W x 1 subwoofer
TOP CAMERA PLATE	-	Yes	
SPECIAL FEATURES	Smart USB Ports	USB 3.2 Gen 1 "SmartPort USB" to all channels	
	One Click to Cloud Drive	Yes	
	Simple LAN Sharing between IFP and Slot-in Device	USB Type-C 10/100, Android & PC 10/100/1000	
	Light Sensor	1	
POWER	Voltage	100-240VAC +/- 10% Wide Range	
	Consumption	On: 151.24W(Energy Star) Off mode: <0.5W	On: 176W(Energy Star) Off mode: <0.5W
ERGONOMICS	Wall Mount (VESA®)	800 x 600 mm	1000 x 400 mm
OPERATING CONDITIONS	Temperature (°C)	0°C to 40°C	
	Humidity	20% - 80% RH non-condensing	
DIMENSIONS (W x H x D)	Physical (inch / mm)	86.73 x 39.37 x 3.62 in / 2203 x 1000 x 92mm	98.71 x 44.49 x 4.06 in / 2507.2 x 1130.1 x 103.2mm
	Packaging (inch / mm)	92.52 x 44.72 x 8.5 in / 2350 x 1136 x 216mm	105.04 x 51.38 x 11.02 in / 2668 x 1305 x 280 mm
WEIGHT	Net (lb / kg)	147.7lb/ 67kg	201.5lb/ 91.4kg
	Gross (lb / kg)	183lb/ 83kg	255.9lb/116.1kg
REGULATIONS	-	cTUVus,FCC/ICES003, LBL(low blue light filter), FF(Flicker free), CE EMC, CB, RoHS Green BOM, RoHS DoC, ErP, REACH SVHC List, DoC, EEL, WEEE	cTUVus,FCC/ICES003, LBL(low blue light filter), FF(Flicker free), CE EMC, CB, RoHS Green BOM, RoHS DoC, ErP, REACH SVHC List, DoC, EEL, WEEE, BSMI
PACKAGE CONTENTS		<ol style="list-style-type: none"> 3m power cord by ship area Type C cable 1.8m(USB-IF certified) Remote control with AAA battery x 2 3m touch USB cable(USB 2.0) Touch pen x 2 (VB-PEN-002) Quick Start Guide with Compliance statement 	<ol style="list-style-type: none"> RS232 adapter Clamp x 5 Camera Plate x 2 (1 for VB-CAM-201, 1 for UMB202) Screw x 8 (camera 2+2, wall mount 4) HDMI cable 3m (HDMI LA certified)
COMPATIBLE SLOT-IN PC		VPC3X, VPCF5-2A	