

ViewSonic Accessibility Conformance Report

EN 301 549 Edition

(Based on VPAT[®] Version 2.5Rev)

Name of Product / Version:

CDE31 series

CDE4331-1C / VS20679, CDE5531-1C / VS20680, CDE6531-1C / VS20681, CDE7531-1C / VS20682, CDE8631-1C / VS20683, CDE9831-1C / VS20684

CDE14 series

CDE8614-2C / VS20832, CDE7514-2C / VS20830, CDE6514-2C / VS20828, CDE5514-2C / VS20826, CDE5014-2C / VS20824, CDE4314-2C / VS20822, CDE8614-1C / VS20832, CDE7514-1C / VS20830, CDE6514-1C / VS20828, CDE5514-1C / VS20826, CDE5014-1C / VS20824, CDE4314-1C / VS20822, CDE8614-1B / VS20832, CDE7514-1B / VS20830, CDE6514-1B / VS20828, CDE5514-1B / VS20826, CDE5014-1B / VS20824, CDE4314-1B / VS20822

CDE30 series

CDE6530 / VS19114, CDE5530 / VS19113, CDE4330 / VS19112, CDE9830-3B / VS19117, CDE8630-3B / VS19116, CDE7530-3B / VS19115, CDE6530-3B / VS19114, CDE5530-3B / VS19113, CDE4330-3B / VS19112, CDE9830-2B / VS19117, CDE8630-2B / VS19116, CDE7530-2B / VS19115

CDEG3 series

CDE43G3-1C / VS20767, CDE55G3-1C / VS20768, CDE75G3-1C / VS20769, CDE86G3-1C / VS20770, CDE98G3-1C / VS20771, CDE65G3-1C / VS20772, CDE43G3-1M / VS20767, CDE55G3-1M / VS20768, CDE65G3-1M / VS20772, CDE75G3-1M / VS20769, CDE86G3-1M / VS20770, CDE98G3-1M / VS20771

CDE105UW / VS20378

CDE92UW / VS20065

Report Date: June 2025

“Voluntary Product Accessibility Template” and “VPAT” are registered service marks of the Information Technology Industry Council (ITI)

Product Description:

The ViewSonic CDE Series is ideal for corporate and campus communication. With standard interfaces like HDMI and USB-C, it ensures easy and efficient operation. Wireless casting is enabled via myViewBoard Display and vCast for seamless screen sharing. It also supports AirPlay and Chromecast, enabling flexible and unlimited casting possibilities.

Contact Information: ViewSonic Europe Limited

EPREL@viewsoniceurope.com; +31 (0) 650608655

Applicable Standards/Guidelines

This report covers the degree of conformance for the following accessibility standard/guidelines:

Standard/Guideline	Included In Report
Web Content Accessibility Guidelines 2.0	Level A (No) Level AA (No) Level AAA (No)
Web Content Accessibility Guidelines 2.1	Level A (No) Level AA (No) Level AAA (No)
EN 301 549 Accessibility requirements for ICT products and services - V3.1.1 (2019-11) AND EN 301 549 Accessibility requirements for ICT products and services - V3.2.1 (2021-03)	Yes

Terms

The terms used in the Conformance Level information are defined as follows:

- **Supports:** The functionality of the product has at least one method that meets the criterion without known defects or meets with equivalent facilitation.
- **Partially Supports:** Some functionality of the product does not meet the criterion.
- **Does Not Support:** The majority of product functionality does not meet the criterion.
- **Not Applicable:** The criterion is not relevant to the product.
- **Not Evaluated:** The product has not been evaluated against the criterion. This can only be used in WCAG Level AAA criteria.

WCAG 2.1 Report

Table 1: Conformance Criteria, Level A

Refer to Manager VPAT

Refer to AirSync VPAT

Table 2: Conformance Criteria, Level AA

Refer to Manager VPAT

Refer to AirSync VPAT

Note: When reporting on conformance with the WCAG 2.1 Success Criteria, they are scoped for full pages, complete processes, and accessibility-supported ways of using technology as documented in the [WCAG 2.1 Conformance Requirements](#).

EN 301 549 Report

Clause 4: [Functional Performance Statements \(FPS\)](#)

Criteria	Conformance Level	Remarks and Explanations
4.2.1 Usage without vision Where ICT provides visual modes of operation, the ICT provides at least one mode of operation that does not require vision. This is essential for users without vision and benefits many more users in different situations.	Partially Supports	The CDE series currently does not support screen reader integration and therefore does not fully meet non-visual operation requirements. However, we recognize this need and are actively evaluating future options to support electronic screen readers or compatible system modules to enhance accessibility compliance.
4.2.2 Usage with limited vision Where ICT provides visual modes of operation, the ICT provides features that enable users to make better use of their limited vision. This is essential for users with limited vision and benefits many more users in different situations.	Supports	The CDE series supports user adjustments to font size and display resolution. These features allow users with limited vision to enlarge content for better recognition and interaction. Font and resolution settings are applicable within the built-in system as well as for connected external sources, providing basic visibility support for users with low vision.
4.2.3 Usage without perception of colour Where ICT provides visual modes of operation, the ICT provides a visual mode of operation that does not require user perception of colour. This is essential for users with limited colour perception and benefits many more users in different situations.	Supports	All functions and descriptions on the CDE series are conveyed through clear textual information without relying solely on color to indicate status or functionality. Users who are unable to perceive color can still fully understand and operate the display, meeting the accessibility requirement.
4.2.4 Usage without hearing Where ICT provides auditory modes of operation, the ICT provides at least one mode of operation that does not require hearing. This	Supports	The CDE series does not rely on audible prompts or voice-based interaction to convey information or enable operation. All functions and instructions are

Criteria	Conformance Level	Remarks and Explanations
is essential for users without hearing and benefits many more users in different situations.		presented visually through on-screen menus and text. As such, users without hearing can fully operate the device, meeting the requirements.
<p>4.2.5 Usage with limited hearing</p> <p>Where ICT provides auditory modes of operation, the ICT provides enhanced audio features. This is essential for users with limited hearing and benefits many more users in different situations.</p>	Supports	The CDE series does not rely on specific audio frequencies, stereo separation, or voice-only instructions for operation. Users with limited hearing can fully access and operate the system, as all essential information is presented visually. The system supports accessibility for users with partial hearing loss.
<p>4.2.6 Usage with no or limited vocal capability</p> <p>Where ICT requires vocal input from users, the ICT provides at least one mode of operation that does not require them to generate vocal output. This is essential users with no or limited vocal capability and benefits many more users in different situations.</p>	Supports	All operations in the CDE series can be controlled via a Remote Control Unit (RCU), keyboard, or mouse. Speech input is not required for any function. Therefore, users who cannot speak are fully able to operate the device, meeting the accessibility requirement.
<p>4.2.7 Usage with limited manipulation or strength</p> <p>Where ICT requires manual actions, the ICT provides features that enable users to make use of the ICT through alternative actions not requiring manipulation, simultaneous action or hand strength. This is essential for users with limited manipulation or strength and benefits many more users in different situations.</p>	Supports	The CDE series supports external device control, allowing users to operate the display via an external keyboard without requiring fine motor skills or simultaneous key presses. In addition, the product supports Wake-on-LAN (WoL), enabling users to power the display remotely through networked devices. These features ensure that users with limited manipulation abilities can fully operate the device.

Criteria	Conformance Level	Remarks and Explanations
<p>4.2.8 Usage with limited reach</p> <p>Where ICT products are free-standing or installed, all the elements required for operation will need to be within reach of all users. This is essential for users with limited reach and benefits many more users in different situations.</p>	Supports	Users can control power and OSD menu with remote control only. It is operable with limited reach and limited strength.
<p>4.2.9 Minimize photosensitive seizure triggers</p> <p>Where ICT provides visual modes of operation, the ICT provides at least one mode of operation that minimizes the potential for triggering photosensitive seizures. This is essential for users with photosensitive seizure triggers.</p>	Supports	The CDE series supports flicker-free functionality and integrated backlight module. Paired with DC dimming technology, it reduces light-flicker frequency, minimizing the potential to trigger photosensitive seizures.
<p>4.2.10 Usage with limited cognition, language or learning</p> <p>The ICT provides features and/or presentation that makes it simpler and easier to understand, operate and use. This is essential for users with limited cognition, language or learning, and benefits many more users in different situations.</p>	Supports	The CDE series power and OSD key icons are textured. OSD menu also designed with graphics to make user can use easily.
<p>4.2.11 Privacy</p> <p>Where ICT provides features for accessibility, the ICT maintains the privacy of users of these features at the same level as other users.</p>	Supports	CDE series maintains the privacy of users of accessibility features at the same level as other users.

Clause [5: Generic Requirements](#)

Criteria	Conformance Level	Remarks and Explanations
5.1 Closed functionality	Heading cell – no response required	Heading cell – no response required
5.1.2 General	Heading cell – no response required	Heading cell – no response required
5.1.2.1 Closed functionality	See 5.2 through 13	See information in 5.2 through 13
5.1.2.2 Assistive technology	See 5.1.3 through 5.1.6	See information in 5.1.3 through 5.1.6
5.1.3 Non-visual access	Heading cell – no response required	Heading cell – no response required
<p>5.1.3.1 Audio output of visual information</p> <p>Where visual information is needed to enable the use of those functions of ICT that are closed to assistive technologies for screen reading, ICT shall provide at least one mode of operation using non-visual access to enable the use of those functions.</p>	Supports	A remote control unit is provided, offering full operational functionality and all operable parts, including buttons and I/O ports, are located on the side edges of the device, providing more than one mode of operation using non-visual access to enable the use of those functions.
<p>5.1.3.2 Auditory output delivery including speech</p> <p>Where auditory output is provided as non-visual access to closed functionality, the auditory output shall be delivered:</p> <ul style="list-style-type: none"> a) either directly by a mechanism included in or provided with the ICT; or b) by a personal headset that can be connected through a 3,5 mm audio jack, or an industry standard connection, without requiring the use of vision. 	Not applicable	Not applicable
<p>5.1.3.3 Auditory output correlation</p> <p>Where auditory output is provided as non-visual access to closed functionality, and where information is displayed on the screen, the ICT should provide auditory information that allows the user to correlate the audio with the information displayed on the screen.</p>	Not applicable	Not applicable

Criteria	Conformance Level	Remarks and Explanations
<p>5.1.3.4 Speech output user control</p> <p>Where speech output is provided as non-visual access to closed functionality, the speech output shall be capable of being interrupted and repeated when requested by the user, where permitted by security requirements.</p>	Not applicable	Not applicable
<p>5.1.3.5 Speech output automatic interruption</p> <p>Where speech output is provided as non-visual access to closed functionality, the ICT shall interrupt current speech output when a user action occurs and when new speech output begins.</p>	Not applicable	Not applicable
<p>5.1.3.6 Speech output for non-text content</p> <p>Where ICT presents non-text content, the alternative for non-text content shall be presented to users via speech output unless the non-text content is pure decoration or is used only for visual formatting. The speech output for non-text content shall follow the guidance for "text alternative" described in WCAG 2.1 [5] Success Criterion 1.1.1.</p>	Not applicable	Not applicable
<p>5.1.3.7 Speech output for video information</p> <p>Where pre-recorded video content is needed to enable the use of closed functions of ICT and where speech output is provided as non-visual access to closed functionality, the speech output shall present equivalent information for the pre-recorded video content.</p>	Not applicable	Not applicable
<p>5.1.3.8 Masked entry</p> <p>Where auditory output is provided as non-visual access to closed functionality, and the characters displayed are masking characters, the auditory output shall not be a spoken version of the characters entered unless the auditory output is known to be delivered only to</p>	Not applicable	Not applicable

Criteria	Conformance Level	Remarks and Explanations
a mechanism for private listening, or the user explicitly chooses to allow non-private auditory output.		
<p>5.1.3.9 Private access to personal data</p> <p>Where auditory output is provided as non-visual access to closed functionality, and the output contains data that is considered to be private according to the applicable privacy policy, the corresponding auditory output shall only be delivered through a mechanism for private listening that can be connected without requiring the use of vision, or through any other mechanism explicitly chosen by the user.</p>	Not applicable	Not applicable
<p>5.1.3.10 Non-interfering audio output</p> <p>Where auditory output is provided as non-visual access to closed functionality, the ICT shall not automatically play, at the same time, any interfering audible output that lasts longer than three seconds.</p>	Not applicable	Not applicable
<p>5.1.3.11 Private listening volume</p> <p>Where auditory output is provided as non-visual access to closed functionality and is delivered through a mechanism for private listening, ICT shall provide at least one non-visual mode of operation for controlling the volume.</p>	Not applicable	Not applicable
<p>5.1.3.12 Speaker volume</p> <p>Where auditory output is provided as non-visual access to closed functionality and is delivered through speakers on ICT, a non-visual incremental volume control shall be provided with output amplification up to a level of at least 65 dBA (-29 dBPaA).</p>	Not applicable	Not applicable
<p>5.1.3.13 Volume reset</p>	Not applicable	Not applicable

Criteria	Conformance Level	Remarks and Explanations
<p>Where auditory output is provided as non-visual access to closed functionality, a function that resets the volume to be at a level of 65 dBA or less after every use, shall be provided, unless the ICT is dedicated to a single user.</p>		
<p>5.1.3.14 Spoken languages</p> <p>Where speech output is provided as non-visual access to closed functionality, speech output shall be in the same human language as the displayed content provided, except:</p> <ul style="list-style-type: none"> a) for proper names, technical terms, words of indeterminate language, and words or phrases that have become part of the vernacular of the immediately surrounding text; b) where the content is generated externally and not under the control of the ICT vendor, the present clause shall not be required to apply for languages not supported by the ICT's speech synthesizer; c) for displayed languages that cannot be selected using non-visual access; d) where the user explicitly selects a speech language that is different from the language of the displayed content. 	Not applicable	Not applicable
<p>5.1.3.15 Non-visual error identification</p> <p>Where speech output is provided as non-visual access to closed functionality and an input error is automatically detected, speech output shall identify and describe the item that is in error.</p>	Not applicable	Not applicable
<p>5.1.3.16 Receipts, tickets, and transactional outputs</p> <p>Where ICT is closed to visual access and provides receipts, tickets or other outputs as a result of a self-service transaction, speech output shall be provided which shall include all information</p>	Not applicable	Not applicable

Criteria	Conformance Level	Remarks and Explanations
<p>necessary to complete or verify the transaction. In the case of ticketing machines, printed copies of itineraries and maps shall not be required to be audible.</p>		
<p>5.1.4 Functionality closed to text enlargement</p> <p>Where any functionality of ICT is closed to the text enlargement features of platform or assistive technology, the ICT shall provide a mode of operation where the text and images of text necessary for all functionality is displayed in such a way that a non-accented capital "H" subtends an angle of at least 0,7 degrees at a viewing distance specified by the supplier.</p> <p>The subtended angle, in degrees, may be calculated from:</p> $\Psi = (180 \times H) / (\pi \times D)$ <p>Where:</p> <ul style="list-style-type: none"> • ψ is the subtended angle in degrees • H is the height of the text • D is the viewing distance • D and H are expressed in the same units 	Supports	The CDE series provides the text and images of text necessary for all functionality is displayed in such a way that a non-accented capital "H" subtends an angle of at least 0,7 degrees at a viewing distance specified by the supplier.
<p>5.1.5 Visual output for auditory information</p> <p>Where auditory information is needed to enable the use of closed functions of ICT, the ICT shall provide visual information that is equivalent to the auditory output.</p>	Not applicable	Not applicable
<p>5.1.6 Operation without keyboard interface</p>	Heading cell – no response required	Heading cell – no response required
<p>5.1.6.1 Closed functionality</p>	See 5.1.3.1 through 5.1.3.16	See information in 5.1.3.1 through 5.1.3.16
<p>5.1.6.2 Input focus</p> <p>Where ICT functionality is closed to keyboards or keyboard interfaces and where input focus can be moved to a user interface element, it shall be possible to move the input focus away from</p>	Supports	The input focus functionality of the CDE series can be moved away from that element using the same

Criteria	Conformance Level	Remarks and Explanations
that element using the same mechanism, in order to avoid trapping the input focus.		mechanism, in order to avoid trapping the input focus.
<p>5.1.7 Access without speech</p> <p>Where speech is needed to operate closed functions of ICT, the ICT shall provide at least one mode of operation using an alternative input mechanism that does not require speech.</p>	Supports	A remote control unit is provided, offering full operational functionality and all operable parts, including buttons and I/O ports, are located on the side edges of the device, providing more than one mode of operation using non-visual access to enable the use of those functions.
<p>5.2 Activation of accessibility features</p> <p>Where ICT has documented accessibility features, it shall be possible to activate those documented accessibility features that are required to meet a specific need without relying on a method that does not support that need.</p>	Supports	A remote control unit is provided, offering full operational functionality and all operable parts, including buttons and I/O ports, are located on the side edges of the device, providing more than one mode of operation using non-visual access to enable the use of those functions.
<p>5.3 Biometrics</p> <p>Where ICT uses biological characteristics, it shall not rely on the use of a particular biological characteristic as the only means of user identification or for control of ICT.</p>	Not applicable	Not applicable
<p>5.4 Preservation of accessibility information during conversion</p> <p>Where ICT converts information or communication it shall preserve all documented non-proprietary information that is</p>	Supports	Our systems preserve accessibility-related information during transmission or conversion when such data is present. We are also reviewing

Criteria	Conformance Level	Remarks and Explanations
provided for accessibility, to the extent that such information can be contained in or supported by the destination format.		our workflows to enhance future support for accessibility features.
5.5 Operable parts	Heading cell – no response required	
5.5.1 Means of operation Where ICT has operable parts that require grasping, pinching, or twisting of the wrist to operate, an accessible alternative means of operation that does not require these actions shall be provided.	Supports	A remote control unit is provided, offering full operational functionality and all operable parts, including buttons and I/O ports, are located on the side edges of the device, providing more than one mode of operation using non-visual access to enable the use of those functions.
5.5.2 Operable parts discernibility Where ICT has operable parts, it shall provide a means to discern each operable part, without requiring vision and without performing the action associated with the operable part.	Supports	Input controls on the device are operable by touch and are designed to be tactilely discernible without requiring vision. Users can identify the presence and layout of controls by feel before initiating any functions.
5.6 Locking or toggle controls	Heading cell – no response required	Heading cell – no response required
5.6.1 Tactile or auditory status Where ICT has a locking or toggle control and the status of that control is visually presented to the user, the ICT shall provide at least one mode of operation where the status of the control can be determined either through touch or sound without operating the control.	Not applicable	Not applicable
5.6.2 Visual status Where ICT has a locking or toggle control and the status of the control is non-visually presented to the user, the ICT shall provide	Not applicable	Not applicable

Criteria	Conformance Level	Remarks and Explanations
at least one mode of operation where the status of the control can be visually determined when the control is presented.		
<p>5.7 Key repeat</p> <p>Where ICT has a key repeat function that cannot be turned off:</p> <ul style="list-style-type: none"> a) the delay before the key repeat shall be adjustable to at least 2 seconds; and b) the key repeat rate shall be adjustable down to one character per 2 seconds. 	Not applicable	Not applicable
<p>5.8 Double-strike key acceptance</p> <p>Where ICT has a keyboard or keypad, the delay after any keystroke, during which an additional key-press will not be accepted if it is identical to the previous keystroke, shall be adjustable up to at least 0,5 seconds.</p>	Not applicable	Not applicable
<p>5.9 Simultaneous user actions</p> <p>Where ICT has a mode of operation requiring simultaneous user actions for its operation, such ICT shall provide at least one mode of operation that does not require simultaneous user actions to operate the ICT.</p>	Not applicable	Not applicable

Clause 8: [Hardware](#)

Criteria	Conformance Level	Remarks and Explanations
8.1.1 Generic requirements	Heading cell – no response required	Heading cell – no response required
8.1.2 Standard connections Where an ICT provides user input or output device connection points, the ICT shall provide at least one input and/or output connection that conforms to an industry standard non-proprietary format, directly or through the use of commercially available adapters.	Supports	All interfaces of the CDE series conform to industry-standard, non-proprietary formats.
8.1.3 Colour Where the ICT has hardware aspects that use colour, colour shall not be used as the only visual means of conveying information, indicating an action, prompting a response, or distinguishing a visual element.	Supports	All user interface menus and controls use text-based labeling and do not rely on color coding to convey information, actions, or prompts.
8.2 Hardware products with speech output	Heading cell – no response required	
8.2.1.1 Speech volume range Where ICT hardware has speech output, it shall provide a means to adjust the speech output volume level over a range of at least 18 dB.	Supports	The CDE series supports volume control with a maximum output level exceeding 80 dB, ensuring compliance with accessibility requirements for speech output.
8.2.1.2 Incremental volume control Where ICT hardware has speech output and its volume control is incremental, it shall provide at least one intermediate step of 12 dB gain above the lowest volume setting.	Supports	The CDE series supports audio volume adjustment and includes a line-out interface, enabling compatibility with a wide range of assistive listening technologies, including personal amplifiers, telecoil-compatible neckloops, mobile speech output devices, and accessible

Criteria	Conformance Level	Remarks and Explanations
		headphones. This ensures enhanced accessibility for users with hearing impairments and 12 dB gain above the lowest volume setting.
<p>8.2.2.1 Fixed-line devices</p> <p>Where ICT hardware is a fixed-line communication device with speech output and which is normally held to the ear, it shall provide a means of magnetic coupling which meets the requirements of ETSI ES 200 381-1 [2] and shall carry the "T" symbol specified in ETSI ETS 300 381.</p>	Not applicable	Not applicable
<p>8.2.2.2 Wireless communication devices</p> <p>Where ICT hardware is a wireless communication device with speech output which is normally held to the ear, it shall provide a means of magnetic coupling to hearing technologies which meets the requirements of ETSI ES 200 381-2.</p>	Not applicable	Not applicable
<p>8.3 Stationary ICT</p>	Heading cell – no response required	Heading cell – no response required
<p>8.3.2.1 Unobstructed high forward reach</p> <p>Where no part of the stationary ICT obstructs the forward reach, at least one of each type of operable part shall be located no higher than 1220 mm (48 inches) above the floor of the access space. This is shown in Figure 2.</p>	Supports	CDE series is designed to allow operable parts to be installed within reach ranges defined, depending on installation height and configuration in the field.
<p>8.3.2.2 Unobstructed low forward reach</p> <p>Where no part of the stationary ICT obstructs the forward reach, at least one of each type of operable part shall be located no lower than 380 mm (15 inches) above the floor of the access space. This is shown in Figure 2.</p>	Supports	CDE series is designed to allow operable parts to be installed within reach ranges defined, depending on installation height and configuration in the field.

Criteria	Conformance Level	Remarks and Explanations
<p>8.3.2.3.1 Clear space</p> <p>Where an obstruction is an integral part of the stationary ICT and hinders the access to any type of operable part, the ICT shall provide a clear space which extends beneath the obstructing element for a distance not less than the required reach depth over the obstruction.</p>	Supports	CDE series is designed to allow operable parts to be installed within reach ranges defined, depending on installation height and configuration in the field.
<p>8.3.2.3.2 Obstructed (< 510 mm) forward reach</p> <p>Where the stationary ICT has an obstruction which is an integral part of the ICT and which is less than 510 mm (20 inches), the forward reach to at least one of each type of operable part shall be no higher than 1220 mm (48 inches) above the floor contact of the ICT.</p> <p>This is shown in Figure 3 (a).</p>	Supports	CDE series is not intended to be operated using a forward reach. All operable parts, including buttons and I/O ports, are located on the side edges of the device. Users are not required to reach over any portion of the ICT to access these components.
<p>8.3.2.3.3 Obstructed (< 635 mm) forward reach</p> <p>Where the stationary ICT has an obstruction which is an integral part of the ICT and which is not less than 510 mm (20 inches) but is less than 635 mm (25 inches) maximum, the forward reach to at least one of each type of operable part shall be no higher than 1120 mm (44 inches) above the floor contact of the ICT.</p> <p>This is shown in Figure 3 (b).</p>	Supports	All operable parts, including buttons and I/O ports, are located on the side edges of the device. Users do not need to reach over any portion of the equipment to access these components.
<p>8.3.2.4 Knee and toe clearance width</p> <p>Where the space under an obstacle that is an integral part of the stationary ICT is part of access space, the clearance shall be at least 760 mm (30 inches) wide.</p>	Supports	The product is designed as a display and does not include a user-facing workstation or counter area. Users are not intended to interact with the device by positioning their knees or toes underneath it.

Criteria	Conformance Level	Remarks and Explanations
<p>8.3.2.5 Toe clearance</p> <p>Where an obstacle is an integral part of the stationary ICT, a space under the obstacle that is less than 230 mm (9 inches) above the floor is considered toe clearance and shall:</p> <ul style="list-style-type: none"> a) extend 635 mm (25 inches) maximum under the whole obstacle; b) provide a space at least 430 mm (17 inches) deep and 230 mm (9 inches) above the floor under the obstacle; c) extend no more than 150 mm (6 inches) beyond any obstruction at 230 mm (9 inches) above the floor. <p>This is shown in Figure 4.</p>	Supports	The product is designed as a display and does not include a user-facing workstation or counter area. Users are not intended to interact with the device by positioning their knees or toes underneath it.
<p>8.3.2.6 Knee clearance</p> <p>Where an obstacle is an integral part of the stationary ICT, the space under the obstacle that is between 230 mm (9 inches) and 685 mm (25 inches) above the floor is considered knee clearance and shall:</p> <ul style="list-style-type: none"> a) extend no more than 635 mm (25 inches) under the obstacle at a height of 230 mm (9 inches) above the floor; b) extend at least 280 mm (11 inches) under the obstacle at a height of 230 mm (9 inches) above the floor; c) extend at least 205 mm (8 inches) under the obstacle at a height of 685 mm (27 inches) above the floor; d) be permitted to be reduced in depth at a rate of 25 mm (1 inch) for each 150 mm (6 inches) in height. <p>This is shown in Figure 5.</p>	Supports	The product is designed as a display and does not include a user-facing workstation or counter area. Users are not intended to interact with the device by positioning their knees or toes underneath it.
<p>8.3.3.1 Unobstructed high side reach</p>	Supports	CDE series is designed to allow operable parts to be installed within

Criteria	Conformance Level	Remarks and Explanations
<p>Where the side reach is unobstructed or obstructed by an element that is an integral part of the stationary ICT and which is less than 255 mm (10 inches), at least one of each type of operable part shall be within a high side reach which is less than or equal to 1220 mm (48 inches) above the floor of the access space.</p> <p>This is shown in Figure 6.</p>		<p>reach ranges defined, depending on installation height and configuration in the field. The physical buttons are located near the lower side edges of the device. Under proper installation conditions, these buttons are within accessible reach ranges as specified in applicable accessibility standards. Additionally, a remote control unit is provided, offering full operational functionality which enables users with limited mobility or reach to operate the device effectively.</p> <p>Regarding input/output ports, all I/O connections are accessible via standard industry connectors. Users can easily extend these connections using cables or breakout adapters, enabling more convenient and accessible configurations as needed.</p>
<p>8.3.3.2 Unobstructed low side reach</p> <p>Where the side reach is unobstructed or obstructed by an element that is an integral part of the stationary ICT and which is less than 255 mm (10 inches), at least one of each type of operable part shall be within a low side reach which is greater than or equal to 380 mm (15 inches) above the floor of the access space.</p>	<p>Supports</p>	<p>CDE series is designed to allow operable parts to be installed within reach ranges defined, depending on installation height and configuration in the field. The physical buttons are located near the lower side edges of</p>

Criteria	Conformance Level	Remarks and Explanations
<p>This is shown in Figure 6.</p>		<p>the device. Under proper installation conditions, these buttons are within accessible reach ranges as specified in applicable accessibility standards. Additionally, a remote control unit is provided, offering full operational functionality which enables users with limited mobility or reach to operate the device effectively.</p> <p>Regarding input/output ports, all I/O connections are accessible via standard industry connectors. Users can easily extend these connections using cables or breakout adapters, enabling more convenient and accessible configurations as needed.</p>
<p>8.3.3.3.1 Obstructed (≤ 255 mm) side reach</p> <p>Where stationary ICT has an obstruction which is an integral part of the ICT, the height of the obstruction shall be less than 865 mm (34 inches). Where the depth of the obstruction is less than or equal to 255 mm (10 inches), the high side reach to at least one of each type of operable part shall be no higher than 1220 mm (48 inches) above the floor of the access space.</p> <p>This is shown in Figure 7 (a).</p>	Supports	<p>The device housing is less than 10 inches (255 mm) in depth. All operable parts are located no more than 10 inches from the reference plane.</p>
<p>8.3.3.3.2 Obstructed (≤ 610 mm) side reach</p>	Not applicable	Not applicable

Criteria	Conformance Level	Remarks and Explanations
<p>Where stationary ICT has an obstruction which is an integral part of the ICT, the height of the obstruction shall be less than 865 mm (34 inches). Where the depth of the obstruction is greater than 255 mm (10 inches) with a maximum depth of 610 mm (24 inches), the high side reach to at least one of each type of operable part shall be no higher than 1 170 mm (46 inches) above the floor of the access space.</p> <p>This is shown in Figure 7 (b).</p>		
<p>8.3.4.1 Change in level</p> <p>Where stationary ICT has a floor within it, then any change of floor level within it or entering it shall be ramped with a slope no steeper than 1:48. Exceptions: a) If the change in floor level is less than or equal to 6,4 mm (¼ inch) the change may be vertical as shown in Figure 8. b) If the change in floor level is less than or equal to 13 mm (½ inch) the change may have a slope not steeper than 1:2 as shown in Figure 9.</p>	Not applicable	Not applicable
<p>8.3.4.2 Clear floor or ground space</p> <p>Where stationary ICT has an operating area within it, it shall provide a clear floor area that has the minimum dimensions of 760 mm (30 inches) by 1 220 mm (48 inches) from which to operate the ICT.</p> <p>This is shown in Figure 10.</p>	Not applicable	Not applicable
<p>8.3.4.3.2 Forward approach</p> <p>Where the operating area is inside an alcove within the stationary ICT, the alcove is deeper than 610 mm (24 inches), and where a forward approach is necessary, the dimension of the access space shall be a minimum of 915 mm (36 inches) wide.</p>	Not applicable	Not applicable

Criteria	Conformance Level	Remarks and Explanations
This is shown in Figure 11.		
<p>8.3.4.3.3 Parallel approach</p> <p>Where the operating area is inside an alcove within the stationary ICT, the alcove is deeper than 380 mm (15 inches), and where a parallel approach is possible, the dimension of the access space shall be a minimum of 1 525 mm (60 inches) wide.</p> <p>This is shown in Figure 12.</p>	Not applicable	Not applicable
<p>8.3.5 Visibility</p> <p>Where stationary ICT provides one or more display screens, at least one of each type of display screen shall be positioned such that the information on the screen is legible from a point located 1015 mm (40 inches) above the centre of the floor of the operating area).</p>	Supports	CDE series is designed to allow operable parts to be installed within reach ranges defined, depending on installation height and configuration in the field.
<p>8.3.6 Installation instructions</p> <p>Installation instructions shall be made available for all stationary ICT. These instructions shall give guidance on how to install the ICT in a manner that takes into account applicable requirements for accessibility of the built environment as they apply to the installation of the ICT. Where there are no such requirements the instructions should require that the dimensions of the installed ICT conform to clauses 8.3.2 to 8.3.5 of the present document.</p>	Supports	ViewSonic provides product related documents on product websites and an official Support & service web page, provides advisors with information on accessibility and compatibility features. User can visit ViewSonic official website for Service support at: https://www.viewsonic.com/global/support/
8.4 Mechanically Operable parts	Heading cell – no response required	Heading cell – no response required
8.4.1 Numeric keys	Supports	The remote control includes a standard 12-key numeric keypad

Criteria	Conformance Level	Remarks and Explanations
Where provided, physical numeric keys arranged in a rectangular keypad layout shall have the number five key tactilely distinct from the other keys of the keypad.		arranged in a compliant layout. The number five key includes a tactile marker to aid users with visual impairments.
<p>8.4.2.1 Means of operation of mechanical parts</p> <p>Where a control requires grasping, pinching, or twisting of the wrist to operate it, an accessible alternative means of operation that does not require these actions shall be provided.</p>	Supports	A remote control unit is provided, offering full operational functionality which enables users with limited mobility or reach to operate the device effectively. The remote control can be operated with ease without requiring tight grasping, pinching, or twisting of the wrist.
<p>8.4.2.2 Force of operation of mechanical parts</p> <p>Where a control requires a force greater than 22,2 N to operate it, an accessible alternative means of operation that requires a force less than 22,2 N shall be provided.</p>	Supports	The remote control can be operated with ease without requiring a force greater than 22,2 N.
<p>8.4.3 Keys, tickets and fare cards</p> <p>Where ICT provides keys, tickets or fare cards, and their orientation is important for further use, they shall have an orientation that is tactilely discernible.</p>	Not applicable	Not applicable
<p>8.5 Tactile indication of speech mode</p> <p>Where ICT is designed for shared use and speech output is available, a tactile indication of the means to initiate the speech mode of operation shall be provided.</p>	Not applicable	Not applicable

Clause [11: Software](#)

Refer to myViewBoard VPAT

Refer to Manager VPAT

Refer to AirSync VPAT

Clause 12: Documentation and Support Services

Criteria	Conformance Level	Remarks and Explanations
12.1 Product documentation	Heading cell – no response required	Heading cell – no response required
<p>12.1.1 Accessibility and compatibility features</p> <p>Product documentation provided with the ICT whether provided separately or integrated within the ICT shall list and explain how to use the accessibility and compatibility features of the ICT.</p>	Supports	<p>ViewSonic provides product related documents on product websites and an official Support & service web page, provides advisors with information on accessibility and compatibility features.</p> <p>User can visit ViewSonic official website for Service support at: https://www.viewsonic.com/global/support/</p>
<p>12.1.2 Accessible documentation</p> <p>Product documentation provided with the ICT shall be made available in at least one of the following electronic formats:</p> <ul style="list-style-type: none"> a) a Web format that conforms to the requirements of clause 9; or b) a non-web format that conforms to the requirements of clause 10. 	See WCAG 2.1 section	See information in WCAG 2.1 section
12.2 Support Services	Heading cell – no response required	Heading cell – no response required
<p>12.2.2 Information on accessibility and compatibility features</p> <p>ICT support services shall provide information on the accessibility and compatibility features that are mentioned in the product documentation.</p>	Supports	<p>ViewSonic provides product related documents on product websites and an official Support & service web page, provides advisors with information on accessibility and compatibility features.</p> <p>User can visit ViewSonic official website for Service support at:</p>

		https://www.viewsonic.com/global/support/
<p>12.2.3 Effective communication</p> <p>ICT support services shall accommodate the communication needs of individuals with disabilities either directly or through a referral point.</p>	Supports	<p>ViewSonic provides product related documents on product websites and an official Support & service web page, provides advisors with information on accessibility and compatibility features.</p> <p>User can visit ViewSonic official website for Service support at: https://www.viewsonic.com/global/support/</p>
<p>12.2.4 Accessible documentation</p> <p>Documentation provided by support services shall be made available in at least one of the following electronic formats:</p> <ul style="list-style-type: none"> a) a Web format that conforms to clause 9; or b) a non-web format that conforms to clause 10. 	See WCAG 2.1 section	See information in WCAG 2.1 section

Legal Disclaimer (Company)

This Conformance Report is provided by ViewSonic Corporation for informational purposes only. It outlines the product's accessibility features based on evaluations conducted as of the report's publication date. This document does not serve as a legally binding assurance of compliance with any accessibility laws or standards.

The report reflects internal assessments and product specifications available at the time of testing. Accessibility performance may vary depending on software versions, device configurations, operating environments, and assistive technologies used.

While ViewSonic strives to maintain accessibility across its products, the information provided here may become outdated due to future updates or changes. Customizations or modifications made by users, integrators, or third parties may affect accessibility and could render portions of this report inaccurate or no longer applicable.

This document is not intended to replace independent assessments by users or institutions. Customers are encouraged to conduct their own evaluations to determine whether the product meets their accessibility and compliance requirements.

ViewSonic is not responsible for the accessibility or accuracy of any third-party content or services that may be integrated into or used in conjunction with ViewSonic products. Responsibility for such content remains with the original provider, including the management of privacy or consent requirements.

Unless otherwise specified in a written agreement, ViewSonic products and related services are provided "as is." No warranties are expressed or implied, including but not limited to warranties of merchantability, fitness for a particular purpose, non-infringement, or uninterrupted operation.

To the extent allowed by law, ViewSonic will not be liable for any indirect, incidental, special, or consequential damages resulting from the use of or inability to use the product, including but not limited to loss of business, revenue, data, or productivity, even if previously advised of the possibility of such damages.