



ViewSonic  | Business

Extron **AMX**  Q-SYS

CDE14-2C Series 4K Commercial Display

The ViewSonic CDE14-2C Series is a commercial-grade 4K display built for 24/7 operation in offices, retail spaces, transit hubs, and other high-demand environments. Powered by Android 14 (upgradeable to 16) and a quad-core SoC with 4 GB RAM, it offers responsive performance and fast startup. With 500 nits brightness and both landscape and portrait support, it delivers clear, versatile visuals for presentations and signage. Continuous USB playback with signal failover ensures uninterrupted content, while integration with ProAV systems and ViewSonic Manager simplifies setup and remote control.



Fast Warm Boot

Quick startup in under 7 seconds minimizes delays when starting meetings or signage playback.



Commercial-Grade Brightness & 24/7 Reliability

Deliver sharp, consistent visuals around the clock with 500 nits brightness and continuous operation.




Native 4K UHD in Any Orientation

Render high-resolution video, data, and graphics with precise pixel-to-pixel clarity in landscape or portrait.



Remote Device Management

Centrally manage networked displays via Web UI, ViewSonic Manager, or ProAV control systems.



Fail-over (Auto signal detection)

Supports active inputs. (excl. USB Auto Play source)



Secure, Future-Proof Platform

Upgradeable Android 14 OS with quad-core SoC and 4GB RAM delivers smooth, reliable performance.

Explore the CDE14-2C Series Commercial Displays

Specifications and availability are subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. Copyright © 2025, ViewSonic Corporation. All rights reserved.



CDE14-2C Series



Sales Contact Information

Spec Table		CDE4314-2C	CDE5014-2C	CDE5514-2C	CDE6514-2C	CDE7514-2C	CDE8614-2C
Display	Panel Size	43"	50"	55"	65"	75"	86"
	Native Resolution	UHD 3840x2160 (Pixels)					
	Colors	8bit+FRC					
	Brightness	500 nits					
	Typical Contrast Ratio	1200:1	5000:1	1200:1	1500:1	1500:1	1200:1
	Dynamic Contrast Ratio	2000:1	5000:1	2000:1	2000:1	2000:1	2000:1
	Response Time	8ms			11ms		8ms
	Viewing Angles	H = 178, V = 178 typ.					
	Backlight Life	50,000 Hours					
	Surface Treatment	Anti-Glare, 3H hardness					
	Haze	25%					
	Even Bezel (mm)	9.9	9.9	9.9	15.9	15.9	15.9
Orientation	Landscape & Portrait						
Platform	Processor	Quad-Core					
	RAM/ Storage	4G DDR4/ 32GB					
INPUT	HDMI-IN	3 (HDMI 2.1 4K@60Hz*3, HDCP1.4/2.2, supports CEC, HDMI 3 supports ARC)					
	RS232	x1					
	Wifi Slot	x1					
OUTPUT	Audio 3.5mm	x1 (Line out)					
	SPDIF	x1					
LAN	RJ45	x1 (10/100M)					
USB	Type A	x2 (USB2.0 x2, Smart USB)					
	Type C	x1 (DP 1.2, USB 2.0, 15W PD, Ethernet sharing, Smart USB)					
Speakers		10W x 2					
COMPATIBILITY	HDMI	3840X2160 @60Hz					
Embedded OS	Android Version	Android 14 AOSP					
POWER	Voltage	100-240VAC +/- 10% Wide Range					
	Consumption	65.18W	57.27W	66.35W	80.65W	93.89W	120.95W
ERGONOMICS	Wall Mount (VESA®)	200x200 mm	400x400 mm	400x400 mm	600x400 mm	600x400 mm	600x400 mm
OPERATING CONDITIONS	Temperature (°C)	0°C ~ 40°C					
	Humidity	20% ~ 80% RH Non-Condensing					
Support 24/7 (Operating Hours)		Yes					
DIMENSIONS (W x H x D)	Physical (inch/mm)	37.98 x 21.75 x 2.81 in 964.6 x 552.5 x 71.4 mm	44.04 x 25.17 x 2.81 in 1118.6 x 639.2 x 71.4 mm	48.54 x 27.7 x 2.81 in 1233 x 703.5 x 71.4 mm	57.61 x 33 x 3.21 in 1463.3 x 838.3 x 81.6 mm	66.36 x 37.94 x 2.94 in 1685.6 x 963.7 x 74.6 mm	76.02 x 43.37 x 3 in 1930.8 x 1101.7 x 76.1 mm
	Packaging (inch/mm)	41.57 x 24.88 x 6.14 in 1056 x 632 x 156 mm	47.21 x 28.31 x 6.14 in 1202 x 719 x 156 mm	52.44 x 33.03 x 6.14 in 1332 x 839 x 156 mm	64.09 x 37.09 x 7.28 in 1628 x 942 x 185 mm	73.35 x 42.91 x 8.86 in 1863 x 1090 x 225 mm	83.07 x 49.09 x 8.86 in 2110 x 1247 x 225 mm
	Cabinet Depth	71.4 mm			81.6 mm	74.6 mm	76.1 mm
WEIGHT	Net (kg/lb)	9.1kg/ 20.06lb	11.7kg/ 25.79lb	12.95kg/ 28.55lb	23.85kg/ 52.58lb	34.15kg/ 75.29lb	42kg/ 92.59lb
	Gross (kg/lb)	13.04kg/ 28.75lb	16.84kg/ 37.13lb	17.98kg/ 39.64lb	32.16kg/ 70.9lb	48.44kg/ 106.79lb	56.95kg/ 125.55lb
REGULATIONS		cTUVus, FCC/ICES003, Energy star 8, EPEAT Silver, EEL, EMC/CE Report, CB, EAC, UkrSEPRO, RCM, Green BOM, RoHS DoC, ErP-Eco, REACH DoC, SCIP, WEEE report, Annex I, Annex II, TPCH DoC, Packing waste, CA65 DoC					
EPEAT Rating		Silver					
Energy Star version		ES 8.0					
EEL rating		E					
Pro-AV Certification		Extron, AMX, Q-SYS					
PACKAGE CONTENTS		<ol style="list-style-type: none"> 3M power cord Remote control AAA battery x 2 Quick Start Guide RS232 adapter Wall mount Screw x 4 HDMI cable 3 M(HDMI LA certified) Compliance statement 					