



ViewSonic  | Business

ViewSonic® Ultrawide Commercial Displays

Expand the Possibilities

Available in 92" and 105" sizes with a 21:9 aspect ratio, ViewSonic® UltraWide Commercial Displays provide a non-touch 5K resolution screen, ideal for delivering vibrant digital signage and impactful presentations. Built for 24/7 operation, they ensure reliability in corporate and commercial environments.

Microsoft Teams Rooms Front Row Optimized

Show attendees, content, and chat on an expansive 21:9 display, enhancing hybrid meeting inclusivity and collaboration.

24/7 Operation

Engineered for around-the-clock operation, providing reliable communication and performance day and night.

Multi-device Wireless Screen Sharing

Share screens from up to 9 devices wirelessly via vCast for seamless communication and collaboration in meetings.

Incredible 5K Ultra HD Resolution

Deliver sharp, detailed visuals with native 5120 x 2160 resolution for clear viewing across the entire room.

Landscape and Portrait Display Orientation

Display content seamlessly in landscape or portrait orientations with unified bezels and flexible mounting options.

USB-C One Cable Solution

With a USB-C port, connect your laptop to transfer data, charge, stream multimedia, and access Ethernet—all through a single cable.



Spec Table

		CDE92UW	CDE105UW
DISPLAY	Panel Size	92"	105"
	Aspect Ratio	21:9	
	Resolution	WUHD 5120x2160 (Pixels)	
	Colors	1.07G colors	
	Brightness	500nits (typ.)	
	Contrast Ratio	5000:1	
	Backlight Life	50,000hrs	
	Surface Treatment	Panel Hard Coating 3H	
	Bezel	18/18/18/18 mm	
	Orientation	Landscape & Portrait	
PLATFORM	Embedded OS	Android 13	
	Processor	Octa-Core CPU	
	RAM	8GB	
	Storage	128GB eMMC	
INPUT	HDMI-IN	x 4 (1x HDMI 2.1 5K@60Hz/ 3x HDMI 2.1 4K@60Hz)	
	DisplayPort	1	
	Audio	1 (3.5mm phone jack)	
	RS232	1	
	OPS	1 (OPS Slot 80pin)	
	WiFi	1 (Module Slot)	
OUTPUT	HDMI	1	
	Audio	1 (Line Out)	
	SPDIF	1	
LAN	RJ45	1 in 1 out (Android & PC 10M/100M/1000Mbps)	
USB	Type-A	REAR x 1 (USB2.0 support OTG), REAR x 2 (USB 3.2 Gen 1), TOP x 2 (USB3.2 Gen 1) support Smart USB	
	Type-C	REAR x1 (PD100W+ DP1.2 + USB2.0, 100M ethernet) support smart USB (dynamic PD: W/OPS 65W, W/O OPS 100W)	
SPEAKERS	-	20W x 2 + 20W x 1 subwoofer	
POWER	Voltage	100-240VAC +/- 10% Wide Range	
	Consumption	Normal 320W, Max 800W	
ERGONOMICS	Wall Mount (VESA [®])	800 x 600 mm	1000 x 600 mm
Support 24/7 Operation Hours	Yes		
PACKAGE CONTENTS	<ol style="list-style-type: none"> 3m power cord by ship area Type C cable 1.8m(USB-IF certified) Remote control with AAA battery x2 Quick Start Guide RS232 adapter Clamp x 5 Camera Plate x 2(1 for VB-CAM-201, 1 for UMB202) Screw x 8 (camera 2+2, wall mount 4) HDMI cable 3m(HDMI LA certified) Compliance statement 		

Explore the CDEUW Ultrawide Series: <https://vsonic.global/CDEUW>

Specifications and availability are subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. Copyright © 2024, ViewSonic Corporation. All rights reserved.

